PATENT COOPERATION TREATY

PCT

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY (Chapter II of the Patent Cooperation Treaty)

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference PE18834PC00	FOR FURTHER ACTION See Form PCT/IPEA/416						
International application No.	International filing date (day	/month/vear)	Priority date (day/month/year)				
	• • •	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	_				
PCT/SE2003/002083 23-12-2003 - International Patent Classification (IPC) or national classification and IPC							
	r national classification and if	rC					
See Supplemental Box							
Applicant							
Telefonaktiebolaget L	M Eriaggon (nuh	oll et al					
Terefoliaktieboraget in	M Elicsson (pur	T) CC UI					
 This report is the international preliminary examination report, established by this International Preliminary Examining Authority under Article 35 and transmitted to the applicant according to Article 36. 							
2. This REPORT consists of a total	of 6 sheets, in	cluding this cover	sheet.				
3. This report is also accompanied b	y ANNEXES, comprising:						
a. (sent to the applicant and to the International Bureau) a total of 6 sheets, as follows:							
sheets of the	description, claims and/or dra	wings which have	been amended and are the basis of this report				
and/or sheets containing rectifications authorized by this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions).							
		which this Authori	ty considers contain an amendment that goes				
beyond the d	isclosure in the international a	application as filed	, as indicated in item 4 of Box No. I and the				
Supplementa	l Box.						
b. (sent to the Internation	onal Bureau only) a total of (i	ndicate type and n	umber of electronic carrier(s))				
,			and/or tables related thereto, in electronic				
	ed in the Supplemental Box R	Relating to Sequen	ce Listing (see Section 802 of the				
Administrative Instru	uctions).						
 This report contains indications r 	elating to the following items	: -					
Box No. I Basis of	of the report .						
Box No. II Priorit	y		·				
Box No. III Non-es	stablishment of opinion with r	regard to novelty, i	nventive step and industrial applicability				
Box No. IV Lack o	of unity of invention		·				
Box No. V Reason							
Box No. VII Certain	n defects in the international a	application	•				
	n observations on the internati						
Box No. VIII Goldan							
Date of submission of the demand		Date of completion	of this report				
17-06-2005		29-03-2006					
Name and mailing address of the IPEA/SE		Authorized officer					
Patent- och registreringsverket							
Box 5055 S-102 42 STOCKHOLM		Markus Stålö / MRo					
Faccimile No. +46, 8, 667, 72, 88		Telephone No. +46 8 782 25 00					

Facsimile No. +46 8 667 72 88

Form PCT/IPEA/409 (cover sheet) (April 2005)

BEST AVAILABLE COPY

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/SE2003/002083

Supplemental Box

In case the space in any of the preceding boxes is not sufficient.

Continuation of: Cover sheet

International patent classification (IPC)

H04Q 7/38 (2006.01)

H04B 7/02 (2006.01)

BEST AVAILABLE COPY

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/SE2003/002083

Box	No. I	Basis of the report						
1.	With r	egard to the language, this report is based on:						
1.								
	H	the international application in the language in which it was filed a translation of the international application into						
		which is the language of a translation furnished for the purposes of:	,					
		international search (Rules 12.3(a) and 23.1(b))						
		publication of the international application (Rule 12.4(a))						
		international preliminary examination (Rules 55.2(a) and/or 5	5.3(a))					
2.	furnis	With regard to the elements of the international application, this report is based on (replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to this report):						
		the international application as originally filed/furnished						
	\boxtimes	the description:						
		pages 1-16	as originally filed/furnished					
		pages* received by this a received by this a						
	\square	the claims:	iudionty on					
			as originally filed/furnished					
			nded (together with any statement) under Article 19					
			Authority on 17-02-2006					
		pages* received by this	Authority on					
	\boxtimes	the drawings:	·					
		pages 1-9	as originally filed/furnished					
		pages* received by this received by this						
		a sequence listing and/or any related table(s) – see Supplemental Box						
	Ш	a sequence listing allow any related table(s) – see Supplemental Box	Relating to Sequence Disting.					
3.		The amendments have resulted in the cancellation of:						
		the description, pages	4					
		the claims, Nos.						
		the drawings, sheets/figs	*					
		the sequence listing (specify):						
		any table(s) related to the sequence listing (specify):						
4.		This report has been established as if (some of) the amendments a made, since they have been considered to go beyond the disclosure 70.2(c)).	nnexed to this report and listed below had not been as filed, as indicated in the Supplemental Box (Rule					
		the description, pages	<u> </u>					
	the claims, Nos.							
		the drawings, sheets/figs						
		the sequence listing (specify):						
		any table(s) related to the sequence listing (specify):						
*	* If item 4 applies, some or all of those sheets may be marked "superseded."							

AP3 Rec'd PCT/PTO 23 JUN 2000

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/SE2003/002083

Box No. V		Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement				
1.	Statement					
	Novel	ty (N)	Claims Claims	1-39	YES NO	
	Invent	ive step (IS)	Claims Claims	1-39	YES NO	
	Indust	rial applicability (IA)	Claims Claims	1-39	YES NO	

2. Citations and explanations (Rule 70.7)

The claimed invention

The invention concerns a method and device for combining soft information from several base stations and solves the problem with lack of capacity in the transport network, when combining soft information from several base stations in a central node.

The aim of the invention is to improve the capacity of the cellular network.

Prior-art

Reference is made to the following documents:

D1: "Multiuser detection with cell diversity for DS/CDMA systems", by Zhang Q. et al.

D2: "Multiuser detection with base station diversity" Valenti, M.C. et al

D3: US 5539749 A

D4: "Improved soft handoff and macro-diversity for mobile radio", by Papen W.

D5: "Distributed compression for sensor networks", by Kusuma J., et al

D6: "Distributed detection with multiple sensors: Part I-Fundamentals", Viswanathan R. et al.

Document D1 describes a multi-bit soft decision making and decision combining scheme. Different base stations providing cell diversity for a given mobile extract decision statistics from the received signal, quantize them and transmit the quantized statistics to a central processor. Based on the received quantized cell decision statistics, the central processor makes the final decision regarding the information bit stream that the mobile transmits. The quantized cell decision statistics can be considered as soft decisions (see D1 Chapter: I Introduction).

PCT/SE2003/002083

Supplemental Box

In case the space in any of the preceding boxes is not sufficient. Continuation of: $Box\ V$

Documents D2, D3 and D4 describe, as in document D1, a soft decision and combining scheme providing cell diversity. Documents D1, D2, D3 and D4 are considered to contain equivalent techniques.

Documents D5-D6 represents the general state of the art.

Statement of reason

Claims 1, 12, 23, 34 and 37

Document D1 is considered to represent the closest prior art. D1 describes a method for transmitting soft information received at several base stations to a combining unit, wherein the soft information is combined.

The invention according to claim 1 differs from the method in D1 in that the soft information is compressed before being transmitted to the combining unit and decompressed before being combined.

Due to these features, the amount of data being transmitted on the transport network between the base stations and the combining unit is reduced.

Consequently, with the background of D1, the problem is to develop a method which reduces the amount of data being transmitted between the base station and the combining unit.

As the applicant states in response to the written option, the "soft information" transmitted to the combining unit described in D1 is already compressed by quantization to reduce the bandwidth in the transport network.

However, for a person skilled in the art there exist several well-known methods to reduce the amount of data being transmitted between the base station and the combining unit, for example quantization (as in document D1), lossy compression, vector quantization, or Huffman coding, i.e. there exist several data compression methods which a person skilled in the art would choose from.

.../..

PCT/SE2003/002083

Supplemental Box

In case the space in any of the preceding boxes is not sufficient. Continuation of: Box $\,V\,$

Since the application is not about developing a new data compression method but rather using well known compression methods, and since no unexpected effects or properties are seen, the skilled person would regard it as a normal design option to choose one of the well-known compression and decompression methods in order to solve the problem posed.

Thus, the subject-matter of claim 1 does not involve an inventive step.

The same arguments apply, mutatis mutandis, to independent claims 12, 23, 34 and 37.

Claims 2-11, 13-22, 24-33, 35-36 and 38-39
The remaining claims are considered to involve particular detail executions obvious to a person skilled in the art.

2CT / SE 2003 / 0 0 2 0 8 3

10/584129

PE18834

CLAIMSAP3 Rec'd PCT/PTO 23 JUN 2000

1. A multiple path information transfer method in a cellular radio network, including the steps of

receiving, at several receivers connected to a transport network, radio signals representing digital information from at least one signal source;

extracting, from each received radio signal, a corresponding digitized baseband signal that at least partially contains soft information;

compressing at least parts of the soft information of said extracted baseband signals into a de-compressible form to form compressed baseband signals;

forwarding said compressed baseband signals to a combining unit over said transport network;

de-compressing said forwarded signals to at least approximately restore said baseband signals; and

using said de-compressed signals to at least approximately restore said digital information.

- 2. The method of claim 1, including the step of performing noise suppression on at least parts of said extracted baseband signals before compression.
- 3. The method of claim 2, wherein said noise suppression is performed by a posteriori probability filtering.
- 4. The method of claim 3, wherein said noise suppression is performed by maximum a posteriori filtering.
- 5. The method of claim 3, wherein said noise suppression is performed by log maximum a posteriori filtering.
- 6. The method of any of claims 2-5, wherein said noise suppression is performed during soft output demodulation.

30

25

5

10

15

7. The method of any of claims 2-5, wherein said noise suppression is performed on the output signal from a soft output demodulator.

8. The method of claim 1, wherein said compressing step includes vector quantization of at least parts of the soft information.

5

10

15

20

25

30

- 9. The method of claim 1, wherein the compression in said compressing step is lossy.
- 10. The method of claim 1, including the step of selecting compression mode for said soft information at least partially based on at least one feedback signal from said combining unit.
 - 11. The method of claim 1, including the step of selecting compression mode for said soft information at least partially based on channel estimates.
 - 12. A multiple path information transfer system in a cellular radio network, said system including

several receivers (BS-1, ..., BS-N), connected to a transport network, for receiving radio signals representing digital information from at least one signal source:

means for extracting, from each received radio signal, a corresponding digitized baseband signal that at least partially contains soft information;

means (10; 10A, 10B) for compressing at least parts of the soft information of said extracted baseband signals into a de-compressible form to form compressed baseband signals;

means (12, 14) for forwarding said compressed baseband signals to a combining unit over said transport network;

means (16; 16A, 16B) for de-compressing said forwarded signals to at least approximately restore said baseband signals; and

means (18-24) using said de-compressed signals to at least approximately restore said digital information.

PE18834

- 13. The system of claim 12, including a noise suppressor (28, 30) performing noise suppression on at least parts of said extracted baseband signals before compression.
- 14. The system of claim 13, wherein said noise suppression is performed by a posteriori probability filters (28; 30).

5

10

15

- 15. The system of claim 14, wherein said noise suppression is performed by maximum a posteriori filters (28; 30).
- 16. The system of claim 14, wherein said noise suppression is performed by log maximum a posteriori filters (28; 30).
- 17. The system of any of claims 13-16, wherein said noise suppression is performed by soft output demodulators (28).
- 18. The system of any of claims 13-16, wherein said noise suppression is performed by filters (30) filtering output signals from soft output demodulators.
- 20 19. The system of claim 12, including means for vector quantization of at least parts of the soft information.
 - 20. The system of claim 12, wherein said means for compressing is adapted to perform lossy compression.
 - 21. The system of claim 12, including means for selecting compression mode for said soft information at least partially based on at least one feedback signal from said combining unit.
- 22. The system of claim 12, including means for selecting compression mode for said soft information at least partially based on channel estimates.

23. A base station in a digital radio network, said base station including a receiver for receiving a radio signal representing digital information from at least one signal source;

means for extracting a digitized baseband signal, which at least partially contains soft information, from said received radio signal; and

means (10; 10A, 10B) for compressing at least parts of the soft information of said extracted baseband signal into a de-compressible form to form a compressed baseband signal.

24. The base station of claim 23, including a noise suppressor (28, 30) performing noise suppression on at least parts of said extracted baseband signal before compression.

5

- 25. The base station of claim 24, wherein said noise suppression is performed by an a posteriori probability filter (28; 30).
 - 26. The base station of claim 25, wherein said noise suppression is performed by a maximum a posteriori filter (28; 30).
- 27. The base station of claim 25, wherein said noise suppression is performed by a log maximum a posteriori filter (28; 30).
 - 28. The base station of any of claims 24-27, wherein said noise suppression is performed by a soft output demodulator (28).
 - 29. The base station of any of claims 24-27, wherein said noise suppression is performed by a filter (30) filtering output signals from a soft output demodulator (28).
- 30. The base station of claim 23, including means (10; 10A, 10B) for vector quantization of at least parts of the soft information.

- 31. The base station of claim 23, wherein said means for compressing is adapted to perform lossy compression.
- 32. The base station of claim 23, including means for selecting compression mode for said soft information at least partially based on at least one feedback signal from an external unit.

5

10

15

20

25

30.

- 33. The base station of claim 23, including means for selecting compression mode for said soft information at least partially based on channel estimates.
- 34.) A signal combining unit in a cellular radio network, said combining unit including

means (14) for receiving multiple signals from a transport network, each signal at least partially containing compressed soft information;

means (16; 16A, 16B) for de-compressing said soft information to form corresponding de-compressed baseband signals from said received signals, and

means (18-24) for combining said baseband signals based on said decompressed soft information.

- 35. The signal combining unit of claim 34, including at least one lookup table for de-compressing vector quantized soft information.
- 36. The signal combining unit of claim 34, including means for sending at least one control signal to compression units to assist in selecting compression mode for said soft information.
- 37) A signal decoder node in a cellular radio network, said decoder including means (14) for receiving a signal from a transport network, said signal at least partially containing compressed soft information;

means (16; 16A, 16B) for de-compressing said soft information to form a corresponding de-compressed baseband signal from said received signal, and

6

1 7 -02- 2006

means (24) for decoding said de-compressed baseband signal based on said de-compressed soft information.

- 38. The signal decoder of claim 36, including at least one lookup table for decompressing vector quantized soft information.
- 39. The signal decoder of claim 37, including means for sending at least one control signal to a compression unit to assist in selecting compression mode for said soft information.

10